



Model	WV-ST162	WV-ST165	WV-SW172	WV-SW175	WV-SW174W	WV-SF132	WV-SF135	WV-SC384
Sku #	1031260	1031261	1031262	1031263	1031264	1031265	1031266	1031267
Camera Type	800 x 600 Indoor Pan-Tilt	1.3 MP Indoor Pan-Tilt	800 x 600 Outdoor Pan-Tilt	1.3 MP Outdoor Pan-Tilt	1.3 MP Wireless Outdoor Pan-Tilt	VGA Indoor dome	1.3 MP Indoor dome	1.3 MP Indoor PTZ (360° w/ auto flip)
Super Dynamic	No	No	No	No	No	No	No	WDR (8x)
Imaging Device	1/4" MOS Sensor Progressive Scan	1/4" MOS Sensor Progressive Scan	1/4" MOS Sensor Progressive Scan	1/4" MOS Sensor Progressive Scan	1/4" MOS Sensor Progressive Scan	1/5" MOS Sensor Progressive Scan	1/3" MOS Sensor Progressive Scan	1/3" MOS Sensor Progressive Scan
Video Compression	H.264 JPEG	H.264 JPEG	H.264 JPEG	H.264 JPEG	H.264 JPEG	H.264 MPEG-4 JPEG	H.264 MPEG-4 JPEG	H.264 MPEG-4 JPEG
Day/Night	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Removable IR (D&N)	No	No	No	No	No	No	No	No
Auto Back Focus	No	No	No	No	No	No	No	Auto Focus
VIQS	No	No	No	No	No	Yes	Yes	No
Minimum Illumination - Color	0.6 lux	0.6 lux	0.6 lux	0.6 lux	0.6 lux	2.0 lux	0.8 lux	0.6 lux
Minimum Illumination - B/W	0.5 lux	0.5 lux	0.5 lux	0.5 lux	0.5 lux	1.3 lux	0.6 lux	0.5 lux
fps JPEG	30fps (800 x 600)	30fps (1280 x 960)	30fps (800 x 600)	30fps (1280 x 960)	30fps (1280 x 960)	30fps (640 x 480)	30fps (1280 x 960)	30fps (1280 x 960)
fps MPEG-4	30fps (640 x 480)	30fps (640 x 480)	30fps (640 x 480)	30fps (640 x 480)	30fps (640 x 480)	-	-	30fps (640 x 480)
fps H.264	30fps (800 x 600)	30fps (1280 x 960)	30fps (800 x 600)	30fps (1280 x 960)	30fps (1280 x 960)	30fps (640 x 480)	30fps (1280 x 960)	30fps (1280 x 960)
Audio Capability	2-way	2-way	2-way	2-way	2-way	No	No	2-way
SD Memory Card Slot	Yes (SDHC)	Yes (SDHC)	Yes (SDHC)	Yes (SDHC)	No	No	No	Yes (SDHC)
SD Card Recording	30fps (H.264) 1fps (JPEG)	30fps (H.264) 1fps (JPEG)	30fps (H.264) 1fps (JPEG)	30fps (H.264) 1fps (JPEG)	30fps (H.264) 1fps (JPEG)	No	No	30fps (H.264) 1fps (JPEG)
Lens Type	Fixed focal length 1.95mm	Fixed focal length 1.95mm	Fixed focal length 1.95mm	Fixed focal length 1.95mm	Fixed focal length 1.95mm	Fixed focal length 1.95mm	Fixed focal length 1.95mm	4.7mm~84.6mm
Zoom	2x (VGA) Ex zoom	2x (VGA) Ex zoom	2x (VGA) Ex zoom	2x (VGA) Ex zoom	2x (VGA) Ex zoom	N/A	2x (VGA) Ex zoom	18x (1.3MP) optical / 36x (VGA) EX optical / 8x electric
Network	10/100 BASE-TX IP v4/v6	10/100 BASE-TX IP v4/v6	10/100 BASE-TX IP v4/v6	10/100 BASE-TX IP v4/v6	10/100 BASE-TX IP v4/v6	10/100 BASE-TX IP v4/v6	10/100 BASE-TX IP v4/v6	10/100 BASE-TX IP v4/v6
Power	12VDC PoE (IEEE802.3af)	12VDC PoE (IEEE802.3af)	12VDC PoE (IEEE802.3af)	12VDC PoE (IEEE802.3af)	12VDC PoE (IEEE802.3af)	12VDC PoE (IEEE802.3af)	12VDC PoE (IEEE802.3af)	12VDC PoE (IEEE802.3af)
Alarm In-/Outputs	2/1	2/1	2/1	2/1	2/1	No	No	2/1
Max Power Consumption	6.2W (PoE) 430 mA (DC)	6.2W (PoE) 430 mA (DC)	6.2W (PoE) 430 mA (DC)	6.2W (PoE) 430 mA (DC)	6.2W (PoE) 430 mA (DC)	2.2W (PoE)	2.6W (PoE)	10W (PoE) 690mA (DC)
Operating Temperature	32°F ~ 104°F	32°F ~ 104°F	-4°F ~ 122°F	-4°F ~ 122°F	-4°F ~ 122°F	32°F ~ 104°F	32°F ~ 104°F	14°F~122°F
Mobile Phone support	JPEG	JPEG	JPEG	JPEG	JPEG	JPEG	JPEG	JPEG
Security	ID/PWD Host Authentication HTTPS	ID/PWD Host Authentication HTTPS	ID/PWD Host Authentication HTTPS	ID/PWD Host Authentication HTTPS	ID/PWD Host Authentication HTTPS	ID/PWD Host Authentication HTTPS	ID/PWD Host Authentication HTTPS	PTZ/AUX Control ID/ PWD Host Authentication HTTPS
Other Features	Face Detection Face WDR	Face Detection Face WDR	Face Detection Face WDR IP55	Face Detection Face WDR IP55	Face Detection Face WDR IP55	Face Detection ABS (Adaptive Black Stretch)	Face Detection ABS (Adaptive Black Stretch)	Drag and Zoom Image Stabilizer Face Detection Face WDR